


Y-STRAINER FLANGE END

法兰过滤器



特点 Features

- 1/2"~12" (DN15~DN300)
- 工作压力 W.P.: PN16 CLASS 150 10K
- 工作温度 W.T.: 425°C

材料表 Material List

序号No.	零件 PARTS	材料 MATERIAL		
		WCB	CF8	CF8M
1	阀体 BODY	WCB	CF8	CF8M
2	SCREEN	304	304	316
3	垫片 GASKET	PTFE		
4	阀盖 BONNET	WCB	CF8	CF8M
5	螺栓 BOLT	304		
6	螺母 NUT	304		
7	垫片 GASKET	PTFE		
8	PLUG	304	304	316

尺寸 Dimensions PN16

Unit: mm

Nominal Diameter	L	d	D2	D1	D	b	f	n-φd1
15	1/2"	130	15	45	65	95	14	2
20	3/4"	150	20	55	75	105	14	2
25	1"	160	25	65	85	115	14	2
32	1-1/4"	165	32	78	100	135	16	2
40	1-1/2"	200	40	85	110	145	16	3
50	2"	220	50	100	125	160	16	3
65	2-1/2"	250	65	120	145	180	18	3
80	3"	280	80	135	160	195	20	3
100	4"	320	100	155	180	215	20	3
125	5"	340	125	185	210	245	22	3
150	6"	385	150	210	240	280	24	3
200	8"	480	200	265	295	335	26	3
250	10"	545	250	320	355	405	26	3
300	12"	605	300	375	410	460	28	3

尺寸 Dimensions CLASS 150

Unit: mm

Nominal Diameter	L	d	D2	D1	D	b	f	n-φd1
15	1/2"	120	15	35	60.3	90	12	2
20	3/4"	140	20	43	70	100	12.5	2
25	1"	150	25	51	79.4	110	12.5	2
32	1-1/4"	170	32	63.5	88.9	115	13.2	2
40	1-1/2"	190	40	73	98.4	125	14.7	2
50	2"	215	50	92	120.7	150	16.3	2
65	2-1/2"	250	65	105	139.7	180	17.9	2
80	3"	285	80	127	152.4	190	19.5	2
100	4"	300	100	157	190.5	230	24.3	2
125	5"	350	125	185	216	255	24.3	2
150	6"	380	150	216	241.3	280	25.9	2
200	8"	480	200	270	298.5	345	29	2
250	10"	545	250	324	362	405	30.6	2
300	12"	605	300	381	431.8	485	32.2	2

尺寸 Dimensions 10K

Unit: mm

Nominal Diameter	L	d	D2	D1	D	b	f	n-φd1
15	1/2"	120	15	51	70	95	12	1
20	3/4"	140	20	56	75	100	14	1
25	1"	150	25	67	90	125	14	1
32	1-1/4"	170	32	76	100	135	16	2
40	1-1/2"	190	40	81	105	140	16	2
50	2"	215	50	96	120	155	16	2
65	2-1/2"	250	65	116	140	175	18	2
80	3"	285	80	126	150	185	18	2
100	4"	300	100	151	175	210	18	2
125	5"	350	125	182	210	250	20	2
150	6"	380	150	212	240	280	22	2
200	8"	480	200	262	290	330	22	2
250	10"	545	250	324	355	400	24	2
300	12"	605	300	368	400	445	24	3