


2-PC VERTICAL CHECK VALVE THREAD END 3-PC VERTICAL CHECK VALVE THREAD END

二片式立式止回阀、三片式立式止回阀

特点 Features

- 1/4"~2" (DN6~DN50)
- 工作压力 W.P.: 1000WOG (PN63)
- 工作温度 W.T.: -20°C~425°C
- 精密铸造 Investment casting
- 螺纹连接标准 Thread end: ASME B1.20.1 (NPT),
DIN 259 / DIN 2999, BS 21,
ISO 288-1, ISO 7-1



材料表 Material List

序号No.	零件 PARTS	材料 MATERIAL		
1	阀体 BODY	WCB	CF8	CF8M
2	阀瓣 DISC	CF8	CF8	CF8M
3	弹簧 SPRING	304	304	316
4	垫片 GASKET	PTFE		
5	阀盖 BONNET	WCB	CF8	CF8M


尺寸 Dimensions

Unit: mm

尺寸 SIZE		d	L	D
1/4"	DN6	10	52	32
3/8"	DN10	12	52	32
1/2"	DN15	14	60	35
3/4"	DN20	19	69	40
1"	DN25	24	80	46.5
1-1/4"	DN32	31	87	56
1-1/2"	DN40	38	100	67
2"	DN50	49	119	80.5

特点 Features

- 1/2"~2" (DN15~DN50)
- 工作压力 W.P.: 1000WOG (PN63)
- 工作温度 W.T.: -20°C~425°C
- 精密铸造 Investment casting
- 螺纹连接标准 Thread end: ASME B1.20.1 (NPT),
DIN 259 / DIN 2999, BS 21,
ISO 288-1, ISO 7-1



材料表 Material List

序号No.	零件 PARTS	材料 MATERIAL		
1	阀盖 BONNET	WCB	CF8	CF8M
2	垫片 GASKET	PTFE		
3	阀瓣 DISC	CF8	CF8	CF8M
4	弹簧 SPRING	304	304	316
5	阀体 BODY	WCB	CF8	CF8M
6	螺栓 BOLT	304		
7	弹簧垫圈 SPRING WASHER	304		
8	螺母 NUT	304		
9	阀盖 BONNET	WCB	CF8	CF8M

尺寸 Dimensions

Unit: mm

尺寸 SIZE		d	L
1/2"	DN15	14	70
3/4"	DN20	19	77
1"	DN25	24	90
1-1/4"	DN32	31	100
1-1/2"	DN40	38	112
2"	DN50	49	125